



## 8848 Dry Vinyl Tape

High quality non-adhesive soft PVC tape, hand and machine applicable, 85°C.

### FEATURES:

- PVC carrier

### BENEFITS:

- Non-adhesive
- Flame retardant
- Highly conformable
- Soft PVC without adhesive
- Controlled, uniform unwind
- Securely Clings to itself
- Customized to the user's application
- Meet RoHS & REACH



### STANDARD SIZES:

Length: 33m, 43m, 76.2m

Width: 16mm, 19mm, 25mm, 32mm

Core ID: 38mm

### COLORS:

Black      Blue      Yellow

White      Orange

Other sizes and colors are available on request.

**8848**

Properties	Value	Unit	Test Method
Total thickness	0.100±0.02	mm	EN 1942
Tensile strength	>16	N/cm	ISO 29864
Elongation at break	>250	%	ISO 29864
Unwind force			QCT-906(24fts/min)
— hand taping	20~40	OZ/19mm	
	5.5~11.1	N/19mm	
	20~45	OZ/25mm	
	5.5~12.5	N/25mm	
	20~50	OZ/32mm	
	5.5~13.9	N/32mm	
— machine taping	<8	OZ/16mm	
	<2.2	N/16mm	
Flammability	B(self-extinguishing)		GMW 16740 / LV 312
Breakdown voltage	4.5	kV	ASTM D1000
Temperature rating	B:-25~85	°C	GMW 16740 / LV 312

Note: The listed values are required only and not intended to serve as product specifications

**RECOMMENDED USES:**

Designed for wrapping applications. For permanent protection of wire harnesses and cables. Also use for insulating and masking parts in the industrial electroplating industry.

**STORAGE AND SHELF LIFE**

The shelf life of the product is one year when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.

All technical information and data mentioned are provided to the best of our knowledge on the basis of our lab tests believed to be reliable. They shall be considered as typical values and are not appropriate for a specification. Therefore, all statements, technical information and recommendations concerning products sold or samples provided by Avery Dennison Yongle do not constitute a guarantee or warranty. All products are sold with the understanding that the user has independently determined the suitability of such products for its application purposes.

©2021 Avery Dennison Corporation. All rights reserved. Avery Dennison Yongle is a trademark of Avery Dennison Corporation. Pylon and all other Avery Dennison brands, product names or service programs are trademarks of Avery Dennison Corporation.

**Avery Dennison Yongle Tape**

No.9 East Yangi Road, Industrial Park,  
Zhuzhou, Hebei, P.R. China  
Post code: 072750

TEL: 0510-82021817 / 13921396678

For more information on our tapes and adhesive solutions, visit [www.yongletape.com.cn](http://www.yongletape.com.cn)